



Automotive Window Environment

Multiflex® material Range



Multibase Group
#09marcom2.V1
Sept. 2009
www.multibase.com

Automotive Window Environment _ #09marcom2.V2 (Sept 2009)

We Compound Your Creations



AUTOMOTIVE WINDOW ENVIRONMENT

	Fonction	Product Range	Platform	References	Hardness	Density	Process	Key features
Glass encapsulation	Aesthetics	Multiflex® EV	TPE-S	TES A6009 EVO BLK TES A6509 EVO N0208 TES A7510 EVO FXT	60A 68A 75A	0.98 0.91 0.99	Injection	High flow Adhesion onto glass Aesthetics Excellent UV resistance Low Odour Low emissions
Belt line seal Glass run channel	Aesthetics	Multiflex® LC	TPE-S	TES A7009 LC0 BLK	70A	0.98	Extrusion	Aesthetics Excellent UV resistance Low Odour Low emissions
	Weatherseal	Multiflex® CV	TPE-S	TES A7006 CV0 BLK	74A	1.13	Extrusion	Compression set Stress relaxation UV resistance
	Slip coat	Multiflex® PV	TPO	TPO D5005 PV1 BLK	50D	0.95	Extrusion	Low COF Fine thickness extrusion
	Filling	Multiflex® SB	TPE-S	TES A7006 SB0 BLK	70A	1.2	Extrusion	
	Rigid part	Multipro®	P/E	PPC 2005 HB1		1.06	Extrusion	UV resistance Impact resistance
Corner Moulding	Aesthetics	Multiflex® SV	TPE-S	TES A8008 SV1 BLK	80A	0.98	Injection	Aesthetics Excellent UV resistance Low Odour Low emissions
	Low friction	Multiflex® PV	TPE-S	TES A8008 PV1 BLK	80A	0.99	Injection	Low COF Excellent UV resistance
Rear window seal	Weatherseal	Multiflex® LC	TPE-S	TES A5009 LC0 BLK	50A	0.98	Extrusion	Anti-squeaking Aesthetics Excellent UV resistance
A-pillar	Aesthetics	Multiflex® EV	TPE-S	TES A6509 EVO N0208 TES A7510 EVO FXT	68A 75A	0.91 0.99	Injection	Aesthetics Excellent UV resistance High flow
Cowl screen seal	Aesthetics	Multiflex® EV	TPE-S	TES A7510 EVO FXT	75A	0.99	Injection	UV resistance Impact resistance Aesthetics

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Multibase's products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe on any patent. Multibase's sole warranty is that the product will meet the Multibase sales specifications in effect at the time of shipment. The exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

MULTIBASE SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

MULTIBASE DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.